

MULTISCAN MC55v captures barcodes in plastic cards or in any other kind of stiff material such as cardboard, metal and any other on which barcodes can be printed.

MULTISCAN MC55v can count and/or read cards and arrange batches of a certain number of cards.

MULTISCAN MC55v can add a data field through the whole batch at once.

Data from read cards is sent to a PC to be recorded and processed.

It reads the most frequent linear barcodes.

It is an accurate and important tool for the effective control of this kind of values of increasing diffusion in financial and commercial activities.

TECHNICAL FEATURES

- Automatic feeding of different kinds of cards.
- Adjustable document separation according to thickness.
- Automatic error feeding detection.
- Reading speed:
300, 450 barcoded cards/m.
- Host communication.
Type: RS232 (standard)
- Feeding tray capacity: up to 120 cards (0.8 mm thick)
- Reception tray capacity:
up to 120 cards (0.8mm thick)

DOCUMENT SIZE

- Minimum: □
44 mm (1.75") x 76 mm (3")
- Maximum: □
127 mm (5") x 152 mm (6")
- Card thickness: 0.5 mm up to 3 mm

BARCODE

- Readable symbologies: Code 39, Code 128, I2/5, Codabar, UPC/EAN, C93 (optional).
- Readable number of codes: □
6 codes/ piece
- Readable digits: 62 chars./ code
- Maximum code length: 4.5" (114mm)
- Minimum code height: 1/ 2" (12mm)
- Maximum code density: 10 mils.

MULTISCAN®
WORLD WIDE LEADER IN AUTOMATIC
DOCUMENT DATA CAPTURE

1110 Brickell Ave Suite 502.
Miami, FL 33131, U.S.A
Ph. (305) 373 8007. Fax (305) 373 8058
E-mail: Info@multiscan-corp.com
www.multiscan-corp.com

MULTISCAN's policy is to continually improve its products, so it reserves the right to change specifications and design without notice.



MULTISCAN®
WORLD WIDE LEADER IN AUTOMATIC
DOCUMENT DATA CAPTURE

