



## GENERAL PURPOSE CORDED HANDHELD CONTACT LINEAR IMAGER BAR CODE READER

The Touch™ TD1100 series of linear imaging contact readers represent the Datalogic ADC solution for customers who require a cost-effective solution for close contact bar code reading without sacrificing quality and performance.

Designed for low throughput applications within multiple markets, the Touch TD1100 readers provide the guarantee of contact reading with an excellent reading performance on virtually all linear bar codes, including damaged or poorly printed codes.

Small, lightweight and low on energy consumption, the Touch TD1100 readers continue to provide robustness and a 1.5 m / 5.0 ft drop resistance, which is typically included in a higher range of products.

The Touch readers are available with the option of two different sizes of reading windows: 6.5 cm / 2.6 in (Touch 65) or 9.0 cm / 3.5 in (Touch 90), which benefits the user when reading standard or wide bar codes.

The Touch TD1100 65/90 Pro readers provide a complete all-in-one multi-interface solution, including RS-232, USB and Keyboard Wedge Emulation, while the Touch 65/90 Lite readers provide USB or RS-232/Keyboard Wedge interfaces.

An innovative 'read-thru' holder provides the Touch TD1100 readers with hands-free reading capability on documents or small items.

Datalogic's Aladdin™ configuration software provides user-friendly features that simplify the start-up procedure, even for inexperienced users.

The Touch series is available in a black model only, however, additional custom color options are available for a minimum order quantity.

## FEATURES

- Wide reading windows: 6.5 cm / 2.6 in and 9.0 cm / 3.5 in
- Excellent reading performance on damaged or poorly printed bar codes
- Interface options: USB or Keyboard Wedge / RS-232 (Touch 65/90 Lite); USB / RS-232 / Keyboard Wedge (Touch 65/90 Pro)
- Supports GS1 DataBar™ linear codes
- Compact and innovative 'read-thru' holder for hands-free reading capability
- Drop Resistance to 1.5 m / 5.0 ft



## DECODING CAPABILITY

1D / LINEAR CODES	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
POSTAL CODES	Australian Post; British Post; Canadian Post; China Post; Japanese Post; KIX Post; Korea Post; PlanetCode; Postnet; Royal Mail Code (RM4SCC)
STACKED CODES	GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

## ELECTRICAL

CURRENT	Operating (Typical): < 100 mA @ 5 VDC Standby/Idle (Typical): 20 mA @ 5 VDC
INPUT VOLTAGE	5 VDC +/- 0.5 V

## ENVIRONMENTAL

AMBIENT LIGHT	0 - 100,000 lux
DROP RESISTANCE	Withstands repeated drops from 1.5 m / 5.0 ft onto a concrete surface
ESD PROTECTION (AIR DISCHARGE)	16 kV
HUMIDITY (NON-CONDENSING)	5 - 95%
PARTICULATE AND WATER SEALING	IP30
TEMPERATURE	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -4 to 158 °F

## INTERFACES

INTERFACES	RS-232 / Keyboard Wedge: Touch 65/90 Lite RS-232 / USB / Keyboard Wedge Multi-Interface: Touch 65/90 Pro USB: Touch 65/90 Lite
------------	--

## PHYSICAL CHARACTERISTICS

COLORS AVAILABLE	Black; Other colors and custom logo options are available for minimum quantity purchase.
DIMENSIONS	65 Pro & Lite: 16.0 x 8.4 x 5.8 cm / 6.3 x 3.3 x 2.3 in 90 Pro & Lite: 17.0 x 10.4 x 6.7 cm / 6.7 x 4.1 x 2.7 in
WEIGHT	65 Pro & Lite: 130.0 g / 4.6 oz 90 Pro & Lite: 153.0 g / 5.4 oz

## READING PERFORMANCE

LIGHT SOURCE	Illumination: 640 nm LED
PRINT CONTRAST RATIO (MINIMUM)	25%
READ ANGLE	Pitch: +/- 65°; Roll (Tilt): +/- 45°; Skew (Yaw): +/- 70°
READING INDICATORS	Beeper (Adjustable Tone); Good Read LED
RESOLUTION (MAXIMUM)	0.102 mm / 4 mil

## READING RANGES

TYPICAL DEPTH OF FIELD	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. Code 39: 7.5 mils: 0 to 8.1 cm / 0 to 3.2 in Code 39: 10 mils: 0 to 12.0 cm / 0 to 4.7 in EAN13: 13 mils: 0 to 15.0 cm / 0 to 6.0 in
------------------------	---

## SAFETY & REGULATORY

AGENCY APPROVALS	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
ENVIRONMENTAL COMPLIANCE	Complies to China RoHS; Complies to EU RoHS

## UTILITIES

DATALOGIC ALADDIN™	Datalogic Aladdin configuration program is available for download at no charge.
OPOS / JAVAPOS	JavaPOS Utilities are available for download at no charge. OPOS Utilities are available for download at no charge.
REMOTE HOST DOWNLOAD	Lowers service costs and improves operations.

## WARRANTY

WARRANTY	5-Year Factory Warranty
----------	-------------------------

## ACCESSORIES

### Mounts/Stands

- HLD-T010-65 Desk/Wall Holder for Touch 65
- HLD-T010-90 Desk/Wall Holder for Touch 90

