



Bravo Series

	B-615	B-615S	B-815
LCD & Touch Panel			
LCD Panel	15" LED-backlit / CCFL	15" LED-backlit	15" LED-backlit / CCFL
MAX. Resolution	1024 x 768 (Default)		
Brightness	250 cd/m ²		
Touch Screen	5-wire Resistive (RS232) / PCAP (USB)		
System Configuration			
CPU	Intel® Atom™ D525 1.8GHz	Intel® Celeron® J1900 2.0GHz/2.4GHz(burst)	Intel® Celeron® 1.8GHz / Intel® Core™ i3 1.8GHz
System Memory	204Pin DDR3 RAM*2 slots, max. 4GB	204pin DDR3L RAM * 1 slot, max. 8GB	204Pin DDR3 RAM*2 slots, max. 8GB
Graphic Memory	Shared memory up to 224MB		
HDD	1 x 2.5" SATA HDD or 1 x 1.8"/2.5" SSD		
SATA DOM	Support 1GB to 16GB		
I/O Ports			
Parallel Port	1 x LPT port (optional,cable output)		
Serial Ports	3 x DB-9 COM ports (COM1/3/4) 1 x RJ-45 COM port (COM5)	3 x DB-9 COM ports (COM1/2/6) 1 x RJ-45 COM port (COM4)	
	(All with DC 5V/12V output on Pin 9 selectable)		
USB Ports	6 x USB 2.0 ports		
LAN Port	1 x (10/100/1000M bps auto)		
Keyboard Port	1 x PS/2 keyboard		
Audio Port	1 x Line out		
VGA Port	1 x DB-15 VGA port		
Cash Drawer Port	1 x RJ-12 port (12V/24V selectable), B-615S / B-815 with dual cash drawer support		
Speaker Output	2 x 1W speaker		
DC Output	1 x DC 12V output		
Powering System			
Power Supply	External DC power adapter(placed inside the system base) AC 90V to 264V full range		
Power Button	1 x System on/off button		
Brightness Control	Yes		
Physical Dimensions			
Wall mount	VESA 75mm*75mm compliant		
System Dimension (L x W x D)	Desktop model: 300*348*218mm, VESA model: 267*348*75mm		
System Weight	Desktop model: 6.7Kg (with integrated adapter), VESA model: 4.7Kg		
Safety & Environment			
Product Certification	CE / FCC / CCC / CB / BSMI / LVD Certified		
Operation Temperature	0°C to 40°C		
Storage Temperature	-25°C to 70°C		
O/S Compatibility	Windows XP / Windows 7 / WEPOS / POSReady 2009/ POSReady 7 / Linux Kernel 2.6 or above	Windows 7 / POSReady 7 / Windows 8.1 Industry / Linux Kernel 2.6 or above	Windows XP / WEPOS / POSReady 2009 / Windows 7 / POSReady 7 / Windows 8.1 Industry / Linux Kernel 2.6 or above



BRAVO SERIES

[15" stylish, energy efficient
scalable touch POS terminal]

Available with PCAP Technology



Precise & Responsive



scratch-resistant



Unlimited touches



Best clarity



[Friendly I/O]



The compact aluminum stand features the adapter inside, not only reducing visual clutter but giving a durable touch experience



01 Stylish, yet versatile design

The design in mate black with silver-glitter accent creates an image of an exquisite work of craftsmanship, giving an elegance appeal of a POS system. A clean and seamless form language is arranged in ways that enhance productivity with a emphasis on space-saving and clutter-free design.

Flexibility and future-proof

Crafted with a easy detachable and field replaceable system core engine, Bravo delivers great utility to meet today's

demands, as well as scale for tomorrow's emerging applications.

02

Engineered to perform

Equipped mobile Intel® processors, Bravo is optimized for excellent balance of energy efficiency and business-optimized performance.

[Tool-free access to the components]



03 Fits anywhere you put it

Easily transition from desktop to pole mount or wall mount.

04 Tailored to meet your ever-changing needs

Enable rapid deployment and fast integration in diverse business projects.



[Identification reader
2-in-1 reader]



[VFD/LCM/8"/10"/15" Customer-facing display]

