

Specifications



Bravo Plus Series

Model number	BP-615	BP-615S	BP-815
LCD & Touch Panel			
LCD Panel	15" LED-backlight		
MAX. Resolution	1024 x 768 (Default)		
Brightness	250 cd / m ²		
Touch Screen	Flat Resistive		
System Configuration			
CPU	Intel® Atom™ D525 1.8GHz (Dual-core)	Fanless Intel® Celeron® J1900 2.0 / 2.4GHz (burst) (Quad-core)	Intel® Celeron® 1.8GHz Intel® Core™ i3 1.8GHz
System Memory	204Pin DDR3 RAM x 2 slots, Up to 4GB	204Pin DDR3L RAM x 1 slot, Up to 8GB	204Pin DDR3 RAM x 2 slots, Up to 8GB
HDD	1 x 2.5" SATA HDD / SSD		
SATA DOM	Support 1GB to 16GB		
I/O Ports			
Parallel Port	1 x LPT port (optional, cable output)		
Serial Ports	3 x DB-9 COM ports (COM1/3/4) 1 x RJ-45 COM port (COM5)	3 x DB-9 COM ports (COM1/2/6) 1 x RJ-45 COM port (COM4)	
	(All with DC 5V/12V output on Pin 9 selectable)		
USB Ports	6 x USB 2.0 ports		
LAN Port	1 x (10 /100 /1000M bps auto)		
Keyboard Port	1 x PS/2 keyboard		
Audio Port	1 x Line out		
VGA Port	1 x DB-15 VGA port		
Cash Drawer Port	1 x RJ-12 port (12V / 24V selectable)		
Speaker Output	2 x 1W speaker		
DC Output	1 x DC 12V output		
Powering System			
Power Supply	External DC power supply (placed inside the system base) AC 90V to 264V full range		
Power Button	1 x System on/off button		
Brightness Control	Yes		
Physical Dimensions			
Wall mount	VESA 75 x 75mm compliant		
System Dimension (L x W x D)	Desktop model : 321 x 360 x 199mm / VESA model : 284 x 360 x 75mm (without stand)		
System Weight	Desktop model : 9Kg / VESA model : 6Kg		
Safety & Environment			
Product Certification	CE / FCC / CCC / CB / BSMI / LVD Certificated		
Operation Temperature	0°C to 40°C		
Storage Temperature	-25°C to 70°C		
OS Compatibility	Windows XP / Windows 7 / WEPOS / POSReady 2009 / POSReady 7 / Linux Kernel 2.6 or above	Windows 7 / POSReady 7 / Windows 8.1 Industry / Windows 10 / Linux Kernel 2.6 or above	Windows XP / WEPOS / POSReady 2009 / Windows 7 / POSReady 7 / Windows 8.1 Industry / Linux Kernel 2.6 or above

BRAVO PLUS



15" energy efficient, bezel-free touch POS terminal

01 Stylish, yet partical design

A clean and seamless form language is arranged in ways that enhance productivity with a emphasis on space-saving and clutter-free design.

Bezel-free touchscreen

The edge-to-edge display design offers higher level of ingress protection.



The heavy-duty aluminum stand features a power adapter inside.

Friendly USB ports

02 Flexible & Future-proof

The modular design allows you to easily leverage the latest performance and usability enhancements, reducing the total cost of ownership.



Easy-detachable system core engine

Energy-efficient, Dual core solution

- Intel® ATOM™ D525 1.8GHz CPU

Fanless, Quad core solution

- Intel® Celeron® J1900 2.0GHz/2.4GHz (burst) CPU

Mobile processor solution

- Intel® Celeron® 1.8GHz CPU
- Intel® Core™ i3 1.8GHz CPU



03 Fits anywhere you put it

Supporting VESA mount for extended use and application.



04 Provides everything you need in a POS

The peripherals are engineered for optimal functionality and compatibility within the system.

Customer-facing display

- VFD/LCM
- 8"/10"/15" 2nd LCD (optional w/ touch)



2-in-1 identification reader

