

▶ dualys ◀

The dual-sided color
plastic card printer



Color & Monochrome
Thermal Transfer



300 dpi



Dual-Sided



29 seconds/card
(YMCKO/K)



0.25-1 mm
(10-40 mil)



2 years

evOLIS

www.evolis.com



With its speed, high-quality printing, numerous encoding capabilities and user-friendliness, the Dualys is the best dual-sided card customization solution on the market.

Just as effective for monochrome thermal transfers as it is for color dye sublimation, the Dualys produces high-resolution prints that are comparable to photographic quality.

Absolutely versatile, the Dualys includes the latest magnetic stripe, smart card or contactless encoding options. All of these encoding techniques are combinable, which allows you to customize your production of sophisticated cards in a single pass. In addition to its 100-card feeder box, its optional manual card feeder instantly turns the Dualys into a front-desk printer.

All of these possibilities pave the way for innovative applications in many sectors: identification, biometric security, leisure, loyalty, transportation, education and banking.

Effective, versatile and user-friendly, the Dualys dual-sided color printer is the ideal solution for all your needs, from timely printing to high-volume customization.



Print mode

- Color dye sublimation and monochrome thermal transfer
- Edge-to-edge printing standard

Printer specifications

- Dual-sided printing module
- Integrated ribbon saver for monochrome printing

Print speed

- 150 cards/hour in full color (YMCKO), one side
- 125 cards/hour in full color (YMCKO/K), two sides
- Up to 1000 cards/hour in monochrome¹, one side
- Up to 350 cards/hour in monochrome¹, two sides

Resolution

- 300 dpi (11,8 dots/mm)

Software supplied

- eMedia Card Designer Software to design and issue badges
- Compatible with Windows™ NT 4.0 / 2000 and Xp

Windows™ drivers

- For Windows™ NT 4.0 / 2000 and Xp

Warranty

- Printer: 2 years
- Print head: 2 years, unlimited number of prints²

Ribbon types

- Monochrome: 1000 cards/roll (black, blue, red, green, white, gold, silver and scratch off)
- BlackWAX monochrome ribbon (for ABS and special varnished cards): 1000 cards/roll
- 2 panel black monochrome ribbon (KO): 500 cards/roll
- 5 panel color ribbon (YMCKO): 200 cards/roll
- Half-panel color ribbon (YMCKO): 400 cards/roll
- 6 panel color ribbon (YMCKO/K): 200 cards/roll
- Hologram ribbon: 350 cards/roll

Card loading modes

- Automatic with feeder or hand-feed

Options

- Serial port (available upon study)
- Manual card feeder
- 100-card additional feeder
- Cleaning kits

Other models

- **Dualys Mag**
Printer with HICO/LOCO magnetic stripe encoder - ISO 7811 or JIS7
- **Dualys Smart**
Printer with smart card contact station - ISO 7816-2
Printer with smart card contact station and EMV 2000 coupler
- **Dualys Contactless**
Printer with Contactless smart card coupler - ISO 14443 - ISO 15693 (other standards upon request)

1 - Under specific conditions
2 - Clause governing the use of Evolis consumables

Card types

All PVC, Composite PVC, PET, ABS and special varnished cards

Card format

ISO CR-80 - ISO 7810 (53,98 mm x 85,60 mm - 3.375" x 2.125")

Card thickness

From 0,25 mm (10 mil) to 1 mm (40 mil)

Card feeder capacity

300 cards (0,25 mm - 10 mil) - 100 cards (0,76 mm - 30 mil)

Card output hopper capacity

300 cards (0,25 mm - 10 mil) - 100 cards (0,76 mm - 30 mil)

Printer size

Height: 235 mm (9.25") - Length: 447 mm (17.59") - Width: 237 mm (9.33")

Printer weight

7,4 Kg (16.31 lbs)

Connections

USB and parallel Centronics ports (cables supplied)

Electrical

110~230 Volts CA, 60~50 Hertz

Environmental

- Min / max operating temperature: 15° / 30° C (59° / 86° F)
- Humidity: 20% to 65% non-condensing
- Min / max storage temperature: -5° / +70° C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air

