Epson TM-T70II Series



DATASHEET



The TM-T70II is the reliable thermal receipt printer that can be fully operated from the front, thanks to its front paper loading. With a small footprint, and accessible button controls, it conveniently sits under your counter, while its fast 250mm per second print speed and margin-less printing allow you to serve your customers quickly – without having to replace paper rolls quite so often.

Easy-to-use

Ideal for restaurants, retailers and the hospitality industry, this POS receipt printer conveniently sits underneath your counter, as it is the same height as most cash drawers, and saves you valuable desktop space. Combined with a wide range of connectivity options (USB, Ethernet and Wi-Fi) this receipt printer offers you the flexibility to set up and operate wherever is most convenient for you. Wires and cables are also protected from accidental spillages thanks to the optional protective.

Long-lasting

This receipt printer is ideal for busy environments that demand consistent, high volume printing. It features an improved printing mechanism life of up to 17 million lines, as well as a printhead life cycle of 120km and auto cutter that can carry on working for up to 1.7 million transactions.

Save money

With the margin-less paper saving function, you can print receipts right up to the edge. This helps save you money, as you are able to print more receipts per roll, and can be an effective eco-friendly addition to your business.

High quality receipt printouts

The TM-T70II is able to print receipts in different shades of grey. Advanced graphic and barcode printing capabilities allow for highly customized layouts. Logos and promotional messages can be added with ease.







KEY FEATURES

- Front operation
 Front loading paper feed
- Fast print speeds
 Up to 250mm per second
- Small footprint
 Easily fits under most counters
- Greyscale printing
 Add logos and images to materials





PRODUCT SPECIFICATIONS

INTERFACES

Interfaces USB 2.0 Type B, RS-232 (optional), Drawer kick-out, Ethernet interface (100 Base-TX / 10

 ${\tt Base-T)\ (optional),\ Wireless\ LAN\ IEEE\ 802.11a/b/g/n\ (optional),\ Powered\ USB\ (optional),}$

Bluetooth (optional)

POWER

Power Supply PS-180 & EURO AC cable, PS-180 & UK AC cable

Power Consumption standby: 0.1 A, Mean: 2 A

Operatingvoltage 24 V

GENERAL

Product dimensions 125 x 194 x 114 mm (Width x Depth x Height)

Product weight 1.7 kg

Color Epson Dark Gray / Epson Cool White

Noise Level Operation: 55 dB (A)

Installation horizontally, vertically with wall hanging bracket

Interface connectors D.K.D. function

 Humidity
 Operation 10% - 90%, Storage 10% - 90%

 Temperature
 Operation 5° C - 45° C, Storage -10° C - 50° C

FONTS & STYLES

Print Speed 250 mm/sec
Printing Font ANK

Character size 0.99 mm (W) x 2.4 mm (H) / 1.41 mm (W) x 3.39 mm (H)
Character set 95 Alphanumeric, 18 set International, 128 x 43 Graphic

Characters per inch 20 cpi / 15 cpi Dot density 180 dpi x 180 dpi

Printing Characters Text (incl. Euro symbol), Graphics, Barcode

DATA BUFFER

Data Buffer 4 kB or 45 Bytes

OTHER

Warranty 24 months Carry in

Optional warranty extension available

LOGISTICS INFORMATION

Carton Weight 2.8 Kg Multiple Order Quantity 2 Units	
Multiple Order Quantity 2 Units	
Pallet Size Euro 168 Units (24 x 7)	

Epson TM-T70II Series

WHAT'S IN THE BOX

- Cable fixation saddle
- Installation/safety manual
- Main unit
- PS-180 & AC cable
- Power switch cover
- Roll paper
- Setup guide
- User manual (CD)

OPTIONAL ACCESSORIES

- Epson Connector Cover for TM-T70II only ECW C32C814605
- Epson Connector Cover for TM-T70II only EDG C32C814606

For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate.

Web: www.epson.co.uk www.epson.ie

