DVNAO® LabelManager™ (420P

CREATE LABELS FAST WITH SMART KEYS

High-performance label maker allows you to pint barcodes or customized labels with own fonts and graphics.


Features

- Large, 4-Line backlit display
- Long lasting rechargeable battery pack
- PC or MAC[®] connectivity with DYMO[®] Connect
- 30+ ways to format texts
- Print upto 10 copies of the same labels
- Save upto 15 frequently used labels
- Print Barcodes UPC-E, Code 39, Code 128, EAN13, EAN8, UPC-A
- Print upto 3/4 in (19mm) wide labels
- For even more features, download DYMO[®] Connect



ALWAYS USE UTILISEZ TOUJOURS

LABELS ÉTIQUETTES



Single Unit Includes:

- LabelManager 420P
- Rechargeable Lithium-Ion Battery
- D1 Starter Label Cassette, 19mm x 3m Black on White
- Charging Adapter
- USB Cable
- Quick Start Guide
- 2 + 1 Year Limited Warranty*

Kit Includes:

- LabelManager 420P + Softcase Bag
- Rechargeable Lithium-Ion Battery
- 4 x D1 Label Cassettes, 6mm x 7m Black on Clear | 9mm x 7m Black on Yellow 12mm x 7m Black on White | 19mm x 7m Black on Red
- Charging Adapter
- USB Cable
- Quick Start Guide
- 2 + 1 Year Limited Warranty*






| Quick Specs | |
|---------------------------------|-------------------------|
| Unit Dimensions (H x W x L) | 104 x 215 x 57 mm |
| Weight (excluding battery) | 415 g |
| Mac [®] /PC Compatible | Yes via DYMO® Connect |
| Accepts Label Sizes | 6mm, 9mm, 12mm and 19mm |
| Tape Platform | D1, Durables |
| Resolution | 180 dpi |
| Printing System | Thermal Transfer |
| Print Speed | 12 mm/sec |
| Barcodes | Yes |
| Cutter Type | Manual |
| Batteries | Rechargeable |
| Adapter | Yes (included) |
| Networking | No |
| Country of Origin | China |

| ltem Number | Description | Length (cm) | Width (cm) | Height (cm) | QTY | EAN | Customer Price |
|----------------------------|---------------------------|-------------|---------------|----------------|-----|---------------|-------------------|
| S0915490 | LabelManager 420P ABC | 10.0 | 18.7 | 25.0 | 1 | 3501170915493 | |
| S0915480 | LabelManager 420P ABC KIT | 26,5 | 104.0 | 57.0 | 1 | 3501170915486 | |
| Accessories (www.dymo.com) | | | | | | | |
| S0895890 | Charging Adapter | 9.0 | 4.8 | 8.2 | - | - | |

* +1 year if registered on the DYMO® website









DYMO[®] high quality labels are made in Belgium

D1 Standard Polyester Labels

For hundreds of tasks around the office or home office, such as filing, storage and asset tracking. Temperature rating: -18°C to 90° C

| D1 STANDARD LABELS (7 m) | 6 mm | 9 mm | 12 mm | 19 mm |
|------------------------------|----------|----------|----------|----------|
| ABC | S0720780 | S0720680 | S0720530 | S0720830 |
| ABC | S0720770 | S0720670 | S0720500 | S0720820 |
| ABC | S0720790 | S0720730 | S0720580 | S0720880 |
| ABC | - | S0720710 | S0720560 | S0720860 |
| ABC | - | S0720740 | S0720590 | S0720890 |
| ABC | - | S0720720 | S0720570 | S0720870 |
| ABC | - | - | S0720610 | S0720910 |
| ABC | - | S0720690 | S0720540 | S0720840 |
| ABC | - | - | S0720510 | - |
| | - | - | S0720600 | - |
| ABC | - | S0720700 | S0720550 | S0720850 |
| ABC | - | - | S0720520 | - |
| D1 STANDARD MULTIPACKS (7 m) | 6 mm | 9 mm | 12 mm | 19 mm |
| ABC | - | 2093096 | 2093097 | 2093098 |





D1 Durable Vinyl Labels

Industrial strength adhesive helps to ensure labels stay stuck to a variety of surfaces. Temperature rating: -40 $^\circ\text{C}$ to $80\,^\circ\text{C}$

| D1 DURABLE LABELS (3 m) | 12 mm |
|---------------------------|---------|
| ABC | 1978366 |
| ABC | 1978365 |
| ABC | 1978367 |
| D1 DURABLE LABELS (5.5 m) | 12 mm |
| ABC | 1978364 |

D1 Permanent Polyester Labels

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins and more. Temperature rating: -40°C to 150°C*

| D1 PERMANENT POLYESTER (5.5 m) | 12 mm | 19 mm |
|--------------------------------|----------|----------|
| ABC | S0718060 | S0718050 |

*depends on surface

D1 Flexible Nylon Labels

Specifically designed for curved surfaces and wire and cable marking.

Temperature rating: -40°C to 60°C

| D1 FLEXIBLE NYLON (3.5 m) | 12 mm | 19 mm |
|---------------------------|----------|----------|
| ABC | S0718040 | S0718070 |











