

Magellan® 1000i

Omni-Directional Imaging Scanner

Data Sheet



Shown with Optional Stand

Features:

- Aggressive imaging performance and intuitive operation reduces checker training and speeds checkout for better customer service
- New imaging technology eliminates moving parts associated with laser scanners for improved reliability
- Hands-free scanning for small, easily handled items, handheld scanning for bulkier items
- Precise imaging scan volume eliminates misreads caused by stray laser scan lines
- Small footprint and size allow for easy integration into point-of-sale and OEM applications
- Textured grip area and small size allow hands of all sizes to comfortably hold the scanner when needed
- Checkpoint® Systems EAS compatible
- Optional targeted scanning mode for PLU Lists
- Optional tilting stand allows scan volume to be optimized for each user and has screw holes for fixed mounting
- Standard product is available in either Black or Grey. Other colors and custom logo options are available for a minimum quantity purchase. Please contact Datalogic Scanning or your Datalogic Scanning reseller for more information on this service.

Accessories:

- Tilting Riser Stand
- Fixed Mounting Plate

Mechanical

Dimensions	Scanner	Stand	Scanner with Stand
Height	8.3 cm / 3.3"	5.8 cm / 2.3"	14.0 cm / 5.5"
Width	71 cm / 2.8"	74 cm / 2.9"	74 cm / 2.9"
Length	9.5 cm / 3.7"	9.7 cm / 3.8"	9.7 cm / 3.8"
Weight	198 g / 7.0 oz	187 g / 6.6 oz	385 g / 13.6 oz

Environmental

Temperature Rating

Operating: 0° to 40° C / 32° to 104° F

Storage/Transport: -40° to 70° C / -40° to 158° F

Humidity: 5 to 95% NC (non-condensing)

Shock: Multiple 1.2 M / 4 drops

Water & Dust Resistance: IP52

Electrical

Operating Voltages

5.0V model \pm 10%

8.0—14.0V model

Operating Current (idle): < 300mA

Operating Current (label read): < 400mA

Communications

- RS-232
- USB
- IBM USB
- Keyboard Wedge
- Wand Emulation
- IBM 46xx / RS-485

Optical

Scan Pattern: 104 line

Scan Rate: 1,100 digital scan lines/second

Single Line Activation: Optional Button

Scan Volume: 987 cm³ / 60 in³

Minimum Resolution: 5 mil

Print Contrast: 25%

Roll: 0 - 360°

Pitch: \pm 65°

Yaw: \pm 75°

Ambient Light

Indoor: < 6,000 Lux / 557 foot candles

Outdoor: < 86,100 Lux / 7999 foot candles

Depth of Field: Please refer to table below

DEPTH OF FIELD Range Comparisons	
LABEL DENSITY	RANGE
5 mil	0.64 - 4.45 cm / 0.50 - 1.75"
7.5 mil	0.64 - 5.72 cm / 0.25 - 2.25"
10 mil	0 - 12.7 cm / 0 - 5"
13 mil UPC	0 - 15.2 cm / 0 - 6"
20 mil	0 - 17.5 cm / 0 - 6.75"
Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.	

Decoding Capability

The Magellan® 1000i autodiscriminates between the following supported symbologies:

Retail Codes:

- UPC Versions A&E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & C128)
- Dual Bar Codes for Japan (2 label read)
- Reduced Space Symbology (RSS) RSS-14, RSS expanded, and RSS Stacked Omni-directional)
- EAN 8 & 13 with full expansion 8 to 13
- JAN 8 & 13 with full expansion 8 to 13
- EAN/JAN two label
- UCC/EAN 128
- Italian Pharmacode
- Supports GTIN

Industrial Codes:

- Code 39 (with full ASCII)
- Code 128 (Up to 80 characters, including Code 39 conversions)
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- Codabar
- MSI/Plessey

Optional 2D Codes: (available in EU only)

- PDF-417
- Datamatrix

Optional Image Capture:

- JPG image capture feature at 640x480 minimum resolution

Please contact your Datalogic Scanning representative for other available symbologies.

Safety and Regulatory

Electrical: Gost R; TÜV; UL; cUL; NOM

Emissions: Complies to FCC; EN 55022; AS/NZS CISPR 22; VCCI; CNS 13438; ICES-003

Restriction of Hazardous Substances: Complies to EU RoHS



Other

EAS compatibility: Integrated EAS hardware works with Checkpoint® Systems.



DATALOGIC™

Datalogic Scanning, Inc.

Toll free: 1 800 695 5700

International: 1 541 683 5700

E-mail us at: scanning@datalogic.com

www.scanning.datalogic.com



Regional restrictions apply to some optional features.

Copyright © Datalogic Scanning, Inc. 2005-2007. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The Datalogic logo is a trademark of Datalogic S.p.A. • Magellan is registered trademarks of Datalogic Scanning, Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.scanning.datalogic.com. • Product specifications are subject to change without notice.