

METAPACE S-1

GREAT DEAL IN A COMPLETE PACKAGE

TECHNICAL SPECIFICATIONS

PROPERTIES

Type	1D laser
Lightsource	650 nm laser diode
Scan rate	100 scans per second
Print contrast	Min. 30% reflectance
Scanning angle	Roll: $\pm 30^\circ$; pitch: $\pm 65^\circ$; skew: $\pm 60^\circ$
Barcodes supported	UPC/EAN, UPC/EAN with supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128 Full ASCII, Codabar, Inter-leaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, IATA, GS1 DataBar (formerly RSS) variants, Chinese 2 of 5

ELECTRONICS

Laser safety	IEC class 1
Voltage	5% \pm 10% @ 100 mA

INTERFACE

I/F ports	RS232, KBW, USB
-----------	-----------------

SPECIFICS

Impact resistance	1.5 m multiple drops onto concrete
-------------------	------------------------------------

ENVIRONMENT

Operating temperature	0°C – 50°C
Storage temperature	-40°C – 70°C
Humidity	5% – 95% RH (non-condensing)

HOUSING

Dimensions (W x H x D)	60 x 62 x 180 mm
Weight	122 g (without cable)
Colour	Black

WARRANTY

Period	36 months
--------	-----------

HIGHLIGHTS

- + Top price and performance: 1D laser scanner for professional applications
- + Complete USB kit: cable and USB hub included in delivery
- + Top quality: exclusive version of a brand manufacturer
- + Ergonomic and intuitive scanning, efficient plug-and-play concept

