

# OPI3201

2D CMOS imager with auto-focus

RS232

Keyboard Wedge

USB



### + Related products



#### OPI2201

- Cabled device
- 2D CMOS imager
- RS232, Keyboard Wedge, USB



#### OPR3201

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB
- With stand

### Operating indicators

- Visual: 1 LED / large LED (red/green/orange)
- Non-visual: Buzzer

### Operating keys

- Entry options:  
1 scan key

### Communication

- RS232: DB9 PTF connector with external power supply
- Keyboard Wedge: MiniDIN6 F/M connector
- USB: Ver. 1.1, HID/VCP, USB-A connector

### Power

- Voltage requirement: 6V  $\pm$  5% (Keyboard Wedge), 6V (min. 4.5, max. 6.5V) (RS232)
- Current consumption: Max. 350 mA (typical use), max. 85mA (standby)

### 2D Imager Optics

- Light source: Aiming laser diode, illumination LEDs
- Scan method: CMOS area sensor, SXGA (1.3 million pixels), gray scale
- Scan rate: Up to 80 fps (excl. focusing)
- Trigger mode: Manual, multiple read, auto-trigger, stand detection
- Image format: Windows Bitmap, JPEG, TIFF
- Gradulation: 256, 16, 2
- Image output mode: 4 resolutions (full, 1/2, 1/3, 1/4), 2 ranges (horizontal, vertical)
- Reading pitch angle: -40 to 0°, 0 to +40°
- Reading skew angle: -50 to 0°, 0 to +50°
- Reading tilt angle: 360°
- Min. resolution at PCS 0.9: 0.127 mm / 5 mil, \*0.169 mm / 7 mil\*, at Code39 / QR Code and \*Data Matrix\*
- Min. PCS value: 0.45/0.3
- Field of view: Horizontal 40°, Vertical 23°
- Depth of field: at Code 39  
15 - 55 mm / 0.59 - 2.17 in (0.127 mm / 5 mil),  
15 - 200 mm / 0.59 - 7.87 in (0.254 mm / 10 mil),  
90 - 870 mm / 3.54 - 34.25 in (1.0 mm / 39 mil)
- Depth of field: at QR Code  
15 - 170 mm / 0.59 - 6.69 in (0.339 mm / 13 mil)

### Supported Symbolologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-I28 (EAN-I28), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISMN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Intelligent Mail Barcode, Korean Postal Authority code, POSTNET
- 2D code: Aztec Code, Aztec Runes, Chinese Sensible code, Codablock F, Composite codes, Data Matrix (ECC200/ECO-140), Maxi Code (mode 2~5), MicroPDF417, Micro QR Code, PDF417, QR code

### Durability

- Temperature in operation: -5 to 50°C / 23 to 122°F
- Temperature in storage: -20 to 60°C / -4 to 140°F
- Humidity in operation: 5 - 85% (non-condensing)
- Humidity in storage: 5 - 85% (non-condensing)
- Ambient light immunity: Fluorescent 10,000 lx max, Direct sun 100,000 lx max, Incandescent 10,000 lx max
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Vibration test: 10 - 100 Hz with 2G for 1 hour
- Protection rate: IP 42

### Physical

- Dimensions (w x h x d):  
56 x 137 x 112 mm / 2.20 x 5.39 x 4.41 in
- Weight body: Ca. 80 g / 2.8 oz (excl. cable)
- Case: ABS, black or white

### Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS, IEC 62471-1, IEC 60825-1 Class 1, IEC 60950-1

### Enclosed items

- Power supply 90-265V/0.5A, 6V/2A (for RS232 and Keyboard Wedge)

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- |                                              |                               |
|----------------------------------------------|-------------------------------|
| - <b>The Netherlands:</b> Hoofddorp          | - <b>Japan:</b> Warabi City   |
| - <b>France:</b> Issy Les Moulineaux         | - <b>Taiwan:</b> Taipei       |
| - <b>Germany:</b> Dietzenbach                | - <b>P.R.China:</b> Shanghai  |
| - <b>Italy:</b> Villanova di Castenaso (BO)  | - <b>Australia:</b> West Ryde |
| - <b>Sweden:</b> Järfälla                    |                               |
| - <b>United Kingdom:</b> Luton, Bedfordshire |                               |
| - <b>U.S.A.:</b> Renton, WA                  |                               |
| - <b>Brazil:</b> São Paulo                   |                               |

Opticon Sensors Europe B.V  
European headquarters  
Opaallaan 35  
2132 XV Hoofddorp  
The Netherlands  
phone: +31 (0)23-5692700  
fax: +31 (0)23-5638266  
email: sales@opticon.com  
internet: www.opticon.com

**OPTICON**  
WWW.OPTICON.COM