

PowerScan[®] 7000

Industrial Strength Imaging Scanner



Features:

- Solid state design makes the PowerScan 7000 the most rugged and reliable scanner on the market
- Lowest priced full performance industrial handheld scanner on the market
- Best dust and water sealing (IP65) on the market
- Industry leading standard range depth of field (DOF)
- Full multi-interface capability
- Industry Leading Four Year Warranty

Accessories

- Universal Kit
- Scan Stand
- Take Up Reel
- Holster/Fork Lift Mount
- Power Hood

Mechanical

Dimensions

Height: 190 mm / 7.5"
Width: 75 mm / 3.0"
Length: 115 mm / 4.5"

Weight: 312 g / 11 oz (without cable)

Beeper/Speaker: 87 dBA for operator @ 50 cm (typical)

Environmental

Temperature Rating

Operating: -30 to 50°C / -22°F to 122°F
Storage: -40 to 60°C / -40° to 140°F

Humidity: 5 to 95% NC

Shock: Withstands 50 drops from 6.5' / 2 m to concrete

Vibration: Meets MIL-STD-810E

Water & Particulate Sealing: IP65

Optical

Scanning Width: 2" wide at 1" from scanner; 6" wide at 7" from scanner

Minimum Resolution: 4 mil minimum element size

Skew (Yaw): ± 60°

Pitch: ± 65°

Roll: ± 40°

Ambient light capability: Up to 40,000 Lux

Depth of Field: See Depth of Field Table below

DEPTH OF FIELD Range Comparisons	
LABEL DENSITY	STANDARD RANGE
5 mil	76 to 15.2 cm / 3 to 6"
75 mil	51 to 40.6 cm / 2 to 16"
10 mil	3.8 to 55.9 cm / 15 to 22"
13 mil	2.5 to 76.2 cm / 1 to 30"
20 mil	2.5 to 106.7 cm / 1 to 42"
55 mil	51 to 203.2 cm / 2 to 80"

Minimum distance determined by symbol length and scan angle.
Printing resolution, contrast, ambient light, temperature, and scan angle dependant.

Data Sheet

Electrical

Input Voltage: +4 to 14 VDC

Input Power (typical)

Operating (idling with no trigger): 148 W

Standby (idling with no trigger): 0.96 W

Input Current (typical)

Operating (scanning): 295 mA @ 5 VDC

Standby (idling with no trigger): 190 mA @ 5 VDC

Sleep: 1 mA @ 5V

Decoding Capability (autodiscriminates among)

- UPC/EAN/JAN
- EAN 128
- Italian Pharmacode 39
- P2 / P5 add-ons
- MSI/Plessey
- Code 93
- Code 39
- Standard 2 of 5
- Codabar
- Micro PDF
- Code 128
- Code 128 add-ons
- Code 128 ISBT
- PDF-417
- Interleaved 2 of 5
- Code 11
- IATA
- RSS-14/Limited/Expanded (linear & stacked)
- Composites CC-A and CC-B (only RS composites)

Host Communications

RS-232, Keyboard Wedge, USB, Wand Emulation, IBM 46XX, and USB (IBM SurePos).

In addition to standard PC/AT/PS/2, the keyboard wedge interface supports the following: Wyse 55, 60, 120, 150, etc.; IBM 347X/3487/31XX; Digital VT220, 240, 320, 420, 510, 520; Sun 420, ITX, and Sparc 5/10.

Safety & Regulatory

Electrical: Complies to GostR; UL; cUL; EN60950

Emissions: Complies to FCC; EN 55022; CISPR22; VCCI

Laser Classification: CDRH Class II,

(Caution: Laser Radiation - do not stare into beam); IEC 60825 Class 2

Restriction of Hazardous Substances: Complies to EU RoHS



DATALOGIC[™]

Datalogic Scanning, Inc.

Toll free: 1 800 695 5700

International: 1 541 683 5700

E-mail us at: scanning@datalogic.com

www.datalogic.com



Copyright © Datalogic Scanning, Inc. 2006-2007. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The Datalogic logo is a trademark of Datalogic S.p.A. • All brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.datalogic.com. • Product specifications are subject to change without notice.

R40-0135-UK US-F 0407