

## **Professional Address Label Printer with Wireless**



# Professional desktop labelling device, with built-in wireless.

Brother's QL-710W desktop labelling device has builtin wireless networking so the whole office can benefit from its professionally printed, customised labels. Enabling you to print everything from address labels, file labels, round CD labels, shipping labels, to barcode labels.

With easy to change rolls, fast print speeds of 93 labels per minute, and a suite of free software included to help you integrate with Microsoft Word, Excel, Outlook and your corporate network, it's a complete and efficient labelling solution. And with Brother's free iPrint & Label app, you can create and print labels directly from your iOS or Android device.

#### **Key Features**

- Save time up to 93 labels per minute print speed
- Durable Automatic cutter
- Share amongst users with wireless connectivity.
- Versatile Choose from a range of pre-sized and continuous labels for different applications
- print address labels directly from Microsoft Word, Excel and Outlook
- Space-saving compact size

## **Supplies**

#### **Die Cut labels**

Standard address label (400)	29 x 90mm	DK-11201
Large address label (400)	38 x 90mm	DK-11208
Small address label (400)	29 x 62mm	DK-11209
Shipping label (400)	62 x 100mm	DK-11202
File folder label(400)	17 x 87mm	DK-11203
Multi-purpose label (400)	17 x 54mm	DK-11204
Square label (400)	23 x 23mm	DK-11221
CD/DVD label (400)	58mm	DK-11207
Round Label (400)	12mm	DK-11219
Round Label (400)	24mm	DK-11218

#### Continuous-length labels (30.48 meters)

12mm	DK22214	29mm	DK22210
38mm	DK22225	50mm	DK22223
62mm	DK22205		
54mm	Non Adhesiv	Non Adhesive	
62mm	Removable (White)		DK44205
62mm	Removable (Yellow)		DK44605

#### Continuous-length labels (film 15.24 meters)

29mm	DK22211	62mm white	DK22212
62mm Yellow	DK22606	62mm clear	DK22113

# **Optional Extras**

None available



## **Product Specifications**

**Housing Colour** 

Network Protocol

Wireless Security **Label Editing Software** 

**Bar Code** 

**Key Board Number of Keys** 4 (On/Off, Editor Lite, Feed, Cut) Cutter Durable Auto cutter (User irreplaceable) **Auto Half Cutter** Power Internal S/W Power Supply LCD **LED** 2 (STATUS: 3 colour - Green, Red, Orange / Editor Lite: 1 colour - Green) **Print Method** Thermal 300 dpi / 720 dots Print Head **Print Speed** 150 mm (5.9") / sec / 93 standard address labels / min. DK rolls (DK Die-cut Labels / DK Continuous Length Tape) **Roll Type Roll Width** Max. Label width 62mm (2.4") Max. Print Width 59mm (2.3") max. **Printable Label Length** 12.7mm (0.5") - 1m (3') **Printer Driver** QL-710W **Computer Interface** USB and Wireless IEEE 802.11b/g/n Protocol (IPv4) ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/NetBIOS name

Server, TFTP server, SNMPv1/v2c, ICMP

Black and White

Micro), Data Matrix(ECC Square, ECC Rectangular), MaxiCode(Model2, Model3, Model4, Model5) Add-in for Microsoft Win: Word, Outlook, Excel Database file compatibility Win: csv, txt, mdb, xls Mac: csv, txt

# Weights/ Dimensions/ Measures

Dimensions 128mm(W) x 236mm(D) x 153mm(H) Weight 1.2kg (without DK roll)







# What's in the box

resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, FTP,

Software side: CODE39, CODE128, UCC/EAN128(GS1-128), ITF(I-2/5), CODABAR(NW-7), UPC-A, UPC-E, EAN13, EAN8, ISBN-2(EAN13 AddOn2), ISBN-5(EAN13 AddOn5), Laser Barcode, POSTNET, RSS(RSS14 Standard, RSS14 Truncated, RSS14 Stacked, RSS14 Stacked Omni, RSS Limited, RSS Expanded, RSS Expanded Stacked), PDF417(Standard, Truncate, Micro), QR code(Model1, Model2,

Wireless SSID (32 chr), WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES), LEAP, EAP-FA

Win: P-touch Editor ver. 5.0, P-touch Address Book ver. 1.1 Mac: P-touch Editor ver. 5.0

CD-ROM (P-touch Editor 5.0 for Windows, P-touch Address Book 1.1, P-touch Editor 5.0 for Mac, Printer Driver, User's Guide, Software User's Guide) Quick Setup Guide, DK Rolls Line-up Guide USB cable, Warranty card DK-11201 Standard Address Labels (100 labels) DK-22205 (62mm Continuous) Starter roll (8 m) Registration Insertion, AC Power cord, EEE insertion