



Saveo BOLT™ is a next-generation smart barcode scanner for Android®, Windows® and iOS* devices. A universal quick-release mounting system allows for any type of smartphone or tablet to be integrated in seconds, whilst providing interoperability with a growing range of Saveo Scan devices. Flex-Protect 'invisible' device cables allow for your device to fast charge and data to be securely transferred whilst in use, whilst protecting your device's charging port. Use completely wirelessly with a Bluetooth Low Energy connection with instant auto-switching feature. SAVEO-BLT-SCCD has been designed to maximize efficiency in scanning operations that require high performance, 1D scanning capabilities from paper media or digital screens. It excels in inventory control, logistics, retail, manufacturing, field services, warehousing, food industries.

FEATURE HIGHLIGHTS

- **IP67 RATED RUGGED WATERPROOF DESIGN**
- UNIVERSAL QUICK-RELEASE DEVICE MOUNT SYSTEM
- HIGH PERFORMANCE 1D RCCD SAVEO SCCD ENGINE
- SUPPORTS ANDROID®, iOS® AND WINDOWS® DEVICES
- **USB OTG WIRED & BLUETOOTH® CONNECTIVITY**
- DOCKING STATION FOR DUAL FAST CHARGE (INCLUDED)
- INVISIBLE TO-DEVICE CABLE SYSTEM (INCLUDED)
- LED STATUS INDICATOR, AUDIBLE BEEPER
- SCAN OVER 80,000 TIMES ON A SINGLE CHARGE









PART DESCRIPTION	P/N
1D RCCD Saveo BOLT Rugged Barcode Scanner (SAVEO SCCD), Multi-USB Interface, Bluetooth 4.0 BLE, Universal Device Mount, Fast Charging Cradle.	SAVEO-BLT-SCCD
Saveo Flex-Protect™ USB Type-C, Micro and Lightning® Cables.	

info@saveoscan.com www.saveoscan.com USA: +1-720-257-7070

UK: +44-208-099-8071



SPECIFICATIONS

Performance characteristics		
Scan Engine	SAVEO SCCD (1D RCCD Scan Engine)	
Sensor	Linear CCD Sensor (1500px)	
Illumination Element	610nm~640nm Red LED	
Depth of field	50mm - 480mm	
Scan Speed	300times/s	
Aim Assist	Red LED Aim Bar	
Reading angle	Tilt: 360°, pitch: ±55°, skew: ±55°	
Print contrast	≥ 30°	
Indicators	LED status Indictor & Audible Beeper	
Interface	USB HID, USB COM, Bluetooth HID, SPP (BLE)	
Triggering	Manual Scan Trigger + Continuous	

Electrical characteristics	
Input voltage	5 VDC ± 1.0 V
Current - operating	Operating 410mA, Idle 260mA
Battery	Li-ion 3200mah (80,000+ scans on a single charge)
Charge Time	1.5hrs (approx.):,from Low to Max
To-Device Cables (included)	Saveo Flex-Protect™ USB Type-C, Micro and Lightning®
Charging Cradle (included)	USB Type-C + USB Micro cable input ports

Physical characteristics	
Dimensions	145 X 85 X 105 mm (L x W x H)
Weight	460 g +/- 5 g (Without cradle)

User Environment	
Operating temperature	-20° ~ + 50°
Storage temperature	-40° ~ + 70°
Humidity	Up to 95% relative humidity, non-condensing
Ambient Light	Maximum 100,000Lux. (direct sunlight)
Drop Rating	Can withstand multiple drops at a height of 2 meters

Symbologies

EAN-8, EAN-13, Codabar, CODE 11, CODE 39, CODE 93, CODE128, China Post, GS1-128, GS1 Limited, GS1 Omnidirectional, UPC-A, UPC-E, ISBN/ISSN, ISBT, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, MSI Plessey,

Packing details	
Inner Box	1pc/box; 300mm x 250mm x 170mm 900g
Carton	12sets/ctn; 11.8kg/ctn; 690mm×420mm×255mm
Certifications	IP67, FCC, CE, RoHS

UK: +44-208-099-8071

info@saveoscan.com www.saveoscan.com USA: +1-720-257-7070