

CASIO

V-T500

Business support Tablet terminal



SMART_{and} TOUGH

- Tough design withstands 1.0m drop and is IP54 dust/splash proof.
- Easy operation with large 10.1 inch LCD touch panel display
- Exchangeable long life battery
- Android™ platform OS



Slim & Stylish design combined with high performance and various features optimised for business use.

Android™ 4.0 platform Business support tablet with superb 10.1 inch LCD touch panel.
Enhancing your business in various industries such as, retail, maintenance, medical or finance.

Features for sales support

- Stylish design for professional presentations.
- Impact-resistant construction minimises the possibility of breakage.
- Creates a great impression with a bright 10.1 inch LCD display with wide viewing angle.
- Fast and reliable Wireless WAN function (only for WAN model).
- Ideal for electronic catalog with product video presentations.
- Video conferencing using integrated camera is possible.
- Integrated NFC reader/writer. Secure staff login using ID cards.
- Dual input operation - with finger or digitiser pen.
- Programmable keys for flexible configuration.
- HDMI interface for connection to TV or data projector.



Features for consultative selling

- Stylish design for customer-facing sales roles.
- Large and bright LCD screen with wide viewing angle.
- Ideal for electronic catalog solutions to show product details.
- Integrated NFC reader/writer. Ideal for loyalty and membership card schemes.
- Runs for many hours of continuous use with long life exchangeable battery.
- Features grooves to ensure a good grip and reduce the possibility of dropping.
- Various ways to hold the terminal with optional hand-belt and neck strap.



Features for maintenance and medical support services

- High performance environmental protection to assure reliable usage in harsh conditions.
- Fast and reliable Wireless WAN function (only for WAN model).
- Remote instruction and video/document sharing is possible with video communication system.
- Integrated high performance GPS unit.
- Large-LCD screen to facilitate communication with the patient.
- Runs for many hours of continuous use with long life exchangeable battery.
- Car charging system to ensure anytime /anywhere operation.
- Features grooves to ensure a good grip and reduce the possibility of dropping.
- Various ways to hold the terminal with optional hand-belt and neck strap.



* Application software and system configuration need to be developed separately.

Specifications

Model Name		V-T500-GE	V-T500-E
Platform		Android™ 4.0	
CPU		OMAP4460 1.5GHz Dual-core	
Main memory	RAM	1GB	
	FROM	16GB	
Environment	Operating temperature	-20°C to 50°C	
	Drop durability	1.0m	
	Dust/Water-splash proof	IP54 level (compliant with IEC60529 standard)	
Digital Camera	Front Camera	5.0 mega pixels Auto focus Camera	
	Rear Camera	5.0-megapixel autofocus camera with LED light	
NFC reader/writer		NFC (Near Field Communication)/FeliCa®/ISO14443 Type A/ISO14443 Type B/ISO15693	
Sensor	GPS	16 channel-receiver	
	Others	Acceleration sensor, geomagnetic sensor, light sensor	
Input	Finger Touch	6-point multi-touch capacitive touch panel	
	Pen Compatibility	Compatible with a digitizer pen (sold separately)	
	Buttons	Power button, volume button, function button A, function button B, screen lock button (function button C)	
Display	Display	10.1-inch(1280x800) color LCD with LED backlight	
	Indicators	Indicator 1: Battery charging status, Indicator 2: Operating status	
Audio		Microphone: built-in (monaural) Speakers: built-in (stereo) Buzzer: built-in	
Wireless communication	Wireless WAN	HSPA/UMTS/EGPRS (EDGE)/GPRS	
	Wireless LAN (Security: WPA2/AES)	Compliant with IEEE802.11a standard (Maximum: 54 Mbps) Compliant with IEEE802.11b standard (Maximum: 11 Mbps) Compliant with IEEE802.11g standard (Maximum: 54 Mbps) Compliant with IEEE802.11n standard (Maximum: 300Mbps)	
	Bluetooth®	Bluetooth® Ver.4.0+EDR	

Model Name		V-T500-GE	V-T500-E
Interface	Card slots	SD Memory Card (SDHC supported) x1	
	SD	microSD Card (microSDHC Card supported) x1	
	USB	Host : USB2.0 TypeA×1 / Client:USB2.0 Mini-B×1	
	HDMI out	mini HDMI×1	
Power Supply	Main Battery	Power Supply Method	Lithium-polymer battery pack (bundled) or AC adaptor (bundled)
		Operating Period	Approx. 12 hours*1 / Approx. 10 hours*2
	Sub Battery	Charging Method	AC adaptor (bundled) / cradle (sold separately) / cradle-type battery charger (sold separately) / dual battery charger (sold separately)
		Charge Time	Approx. 6 hours
	Backup Duration	After low battery warning: 72 hours; During battery replacement: 10 minutes	
Dimensions/Weight	Dimensions (W×H×D)	Approx. 269 x 14.4 x 19.0mm	
	Weight (Including Battery Pack)	Approx. 780g	
Bundled Accessories		AC adaptor x1, Lithium-polymer rechargeable battery pack x1	

*1: In the case of 3 hours of operation (in which the following cycle is repeated: 3 minutes of 3G Wireless WAN transmission, 1 minute of screen viewing, and 6 minutes of application operation), and 9 hours of standby (3G Wireless WAN standby and screen off). *2: When the following cycle is repeated: 1 minute of data transmission, 1 minute of videoplayback, 3 minutes of screen viewing, and 10 minutes of standby (screen off).

Options

Model	Description
HA-M20BAT	Rechargeable battery pack
HA-M62IO	Ethernet Cradle
HA-M30CHG	Cradle-type battery charger
HA-M32DCHG	Dual battery charger
HA-M37CAC	Car adaptor
AD-S36120A-N	AC adaptor for Ethernet Cradle / cradle-type battery charger
AD-S90190C-N5	AC adaptor for dual battery charger
HA-M95HB	Hand-belt
HA-M98DC	Screen cover
HA-M96PEN	Digitiser pen
HA-M97ST	Neck strap

●Android™ is a trademark of Google Inc. ●FeliCa is a trademark of Sony Corporation. ●The BLUETOOTH registered trademark is owned by Bluetooth SIG, Inc., U.S.A., and licensed to CASIO Computer Co., Ltd.. ●Other company and product names are generally registered trademarks or trademarks of the respective companies. ●The design and specification is tentative and may change without notice. The colour of the product in the picture may be different from the actual product. ●Images on screens are simulated. ●Specifications in the table above are current as of July 2012, and may be changed without prior notice.