


Thanks to the omnidirectional laser pattern the OPM 5135 will read the bar code in any orientation.

Omnidirectional

OPM 5135

Omnidirectional laser scanner



Features

- Omnidirectional scanning
- Scan pattern of several lines
- Different interfaces available
- Compact size
- Data validation

Benefits

- No bar code orientation
- Instant bar code detection
- Easy connectivity RS232, Keyboard Wedge, USB
- Minimum space occupation
- Data output control

Cabled

Wireless

Stationary

OEM

OPTICON
always scanning for new ID's

Specifications

OPM 5135 Omnidirectional laser scanner

Electrical specifications

Voltage requirement	5V \pm 10 %
Current consumption	730 mA max (at reading, communication off)
Idle current	500 mA max

Optical specifications

Light source	650 nm visible laser diode
Scan method	rotating polygon mirror, Pattern of 4 parallel lines in 5 orientations (20 scan lines)
Scan rate	1000 scans/sec
Reading skew angle	+8 - +50°, -8 - -50° (at EAN13 PCS0.9, resolution 0.33, 10% skew, 70mm from window)
Reading rotation angle	360°
Reading tilt angle	\pm 35° (at EAN13 PCS0.9, resolution 0.33, 10% skew, 70mm from window)
Focal plane	70 mm from window
Curvature	R>20 (at EAN8, resolution 0.26mm), R>25 (at EAN13, resolution 0.26mm)
Min. Resolution at PCS 0.9	0.15 mm (6 mil)
Min. PCS value	0.45
Depth of field	10 - 230 mm, depending on reading distance and bar code label resolution

Identification

Supported barcode symbologies	Chinese Post - Codabar ABC and CX - Code 39 incl. full ASCII - Code 93 - Code 128 - EAN-8 incl. +2,+5 - EAN-13 incl. +2,+5 - EAN-128 - IATA - ISBN - ISSN - Industrial 2of5 - Interleaved 2of5 - Italian Pharmaceutical - Matrix 2 of 5 - MSI/Plessey - UK/Plessey - S-Code - Telepen - TriOptic - S-Code - UPC-A incl. +2,+5 - UPC-E incl. +2,+5
-------------------------------	---

Functionality

Interface	Keyboard Wedge: XT/AT and PS2, RS232, USB
-----------	---

Environmental specifications

Temperature in operation	0 - +40 °C
Temperature in storage	-40 - +60 °C
Humidity in operation	20 - 80 % (non condensing)
Humidity in storage	20 - 90 % (non condensing)
Ambient fluorescent light	3.000 lux max
Ambient white light	3.000 lux max
Ambient direct sun light	50.000 lux max

Physical specifications

Dimensions	(l x w x h) 85 x 76 x 96 mm
Weight body	ca. 400 g (excl. cable)
Cable length	2 mtr straight
Connector Keyboard Wedge	DIN 5, MiniDIN 6 with external power
Connector RS232	DB9 F with external power
Connector USB	USB-A with external power

Regulatory

Laser safety class	IEC 825, Class I laserproduct
EMC	EN 55022, EN 55024

